

FRYER, BOILER AND STEAMER COOKING APPARATUS

FIELD OF THE INVENTION

5 The present invention is directed at providing a cooking apparatus which is sufficiently versatile to enable deep frying large/heavy objects such as turkeys, while also providing for steaming and boiling of other food items without introducing added component requirements and the need to assemble multiple components. The present invention is also directed at facilitating the draining of cooking fluid from a cooking basket and/or a pot in which the cooking fluid is provided.

BACKGROUND OF THE INVENTION

10 There exist a variety of cookware, both indoor and outdoor, for deep frying, steaming and boiling food items. Deep frying large poultry items such as whole turkey with an outdoor cooking apparatus has gained in popularity as a way of cooking which is both quicker than baking and less susceptible to drying out the food. Outdoor cooking apparatus often include a stock pot which is received on a gas (e.g., propane) cooker stand. In deep frying a whole turkey, 15 a pot that is sufficiently sized to receive a whole turkey is utilized in conjunction with a sufficient level of cooking oil. To avoid exposure to the oil (e.g. splashing or actual contact), turkey securement arrangements have been developed.

20 Examples of turkey securement arrangements for deep frying turkey cooking apparatus can be found in U.S. Patent Nos. 5,896,810 and 5,813,321. U.S. Patent 5,896,810 describes a perforated turkey support plate with underlying legs to lift the bottom of the supported turkey off the bottom of the pot and a central turkey skewer rod having an upper end lifting loop for hooking engagement with a grab hook. This cooking approach is limited to deep frying a skewered turkey slid down along the skewer rod. Thus, this device is one dimensional and does

not provide a system which provides for steaming or boiling other types of food items (e.g., steaming shelled seafood). Also, having to skewer a turkey requires a large degree of undesirable food handling and can be difficult when dealing with a not entirely thawed turkey or one not having a sufficiently sized or oriented through passage.

5 The cooking apparatus in U.S. Patent No. 5,813,321 is described as being capable of performing either a deep fat frying or steaming function. A frame structure having a turkey penetrator and a pair of vertical members for hook attachment is provided for lifting and dropping a turkey into the oil. To achieve the steaming function, a steamer plate is slid in position inside the vertical members and past a central opening in the plate which receives the turkey penetrator. Thus, while being suited for both steaming and deep frying, there is relied upon multiple components which leads to the potential difficulty of having all components available at the time of desired usage as well as undesirable assembly and disassembly requirements between usage.

10 As further described in the background portion of U.S. Patent No. 5,896,810, conventional deep frying baskets generally have one or two handles located near the top edge of a mesh or perforated basket. U.S. Patent No. 5,896,810, in adapting a skewering alternative to a conventional deep frying basket, points out that the conventional baskets are not appropriate for deep frying turkeys as they are often not strong enough to support a large turkey and the handles end up close to the hot oil which is dangerous in deep fat frying a turkey or the like. There is
15 also often little peripheral room for manipulating such baskets as the stock pots are generally tall
20 and of smaller diameter to facilitate meeting the oil level and cooker sizing requirements

GENERAL DESCRIPTION OF THE INVENTION:

The present invention comprises a cooking apparatus that is particularly well suited for deep frying heavy objects such as a whole turkey and steaming and/or boiling smaller and/or larger food items.

5 The present invention is also directed at facilitating the draining of cooking fluid upon completion of deep fry or boiling or the proper positioning of a cooking basket during a steaming operation. The present invention is also directed at facilitating the drainage of cooking fluid from the pot holding the oil. One embodiment of the cooking apparatus of the present invention comprises a pot with diametrically opposed exterior handles and a lid with its own lid handle. The pot is of relatively large capacity (e.g., 10 to 50 qts. or more preferably 20 to 40 qts.) making it well suited for cooking large objects such as a turkey (e.g., a 10 or more pound turkey, including a 15 or 16 pound turkey, which represents a general upper range for preferred cooking turkey sizes).

10 The cooking apparatus of the present invention further comprises a multi-purpose basket that is sized for reception within the above noted cooking pot, and also has a sufficiently large periphery and depth to receive a large cooking turkey as described above (e.g., basket having an 8 to 12 inch diameter received in a pot having a diameter which provides $\frac{1}{2}$ to $2\frac{1}{2}$ inches of radial clearance relative to a central positioned basket and the interior surface of the cooking pot). This close radial relationship helps minimize the quantity of oil that needs to be placed in
15 the pot to submerge the turkey.
20

As the basket is designed to provide for deep frying heavy objects such as a turkey (including the added weight associated with post cooking absorption of cooking oil) it is preferably formed of unitary metal structure with apertures formed therein and preferably not of

low load wire or metal rod screen or mesh arrangements such as in conventional indoor deep fat fryers. Because of the heavy load possibility the basket is formed of relatively thick aluminum (e.g., at least 1.0 mm thick) material. To maintain sufficient strength there is a greater percentage of solid surface than open surface in the areas where apertures are provided. For example, .3 to .7 inch diameter holes with .7 to 1.5 inch minimum spacing between holes. A series of .5 inch holes with .9 inch minimum spacing covering all surfaces of the basket provides a good high strength/drain-steam arrangement.

The basket has a side wall that is of sufficient height to adequately retain a large turkey in position within the basket despite the turbulent effects of deep fat frying. For example, a height sufficient to extend to or past at least half the lower half of a large vertically oriented turkey in the basket (e.g., 6 to 16 inches) with a height ratio range of 2:8 to 5:8 relative to the cooking pot. A basket height as indicated is also well suited for steaming typical quantities of seafood such as clams and mussels. A basket height (main body) of about 7 to 10 inches which is sufficient to extend to between the 2/3 turkey height to the top of an average height large vertically oriented turkey, is a preferred basket height range for the present invention).

The basket also includes its own handle structure. In one embodiment of the invention, the handle structure includes a unitary U-shaped bailing handle having its free ends either pivotably or rigidly attached to an upper edge region of the basket. The height of the handle above the main body of the basket is preferably less than the height of the upper edge of the cooking pot relative to the upper edge of the main body. The free ends of the bailing handle are preferably permanently secured to the basket to avoid inadvertent (manual) detachment (e.g. a sufficiently closed loop arrangement or permanent weld or bulbous captured end). The bailing handle has a capture receptor in an upper region for facilitating placement and location of a

grasping handle relative to the bailing handle structure. In one embodiment the capture recess is a centralized V-shaped or C-shaped bend region designed for facilitating a grasping hook capture relationship when using a unitary bailing handle. In another embodiment, the handle structure comprises a pair of upstanding (e.g. vertical) bars rigidly fixed to the basket's main body.

- 5 Engagement means such as loops are provided at the free end of the diametrically opposed pair of upstanding bars. For this embodiment, the grasping handle comprises a U-shaped dual extension grasping hook arrangement which places two vertical hook extensions at the same diametrical spacing as the loops provided at the free ends of the upstanding bars.

The basket further comprises at least one drain/steamer capture device which comprises a hook or clamp arrangement supported on the upper edge of the main body of the basket (e.g., within the upper half of a basket side wall) and preferably with at least one capture device within the upper 20% of the basket's height. The drain/steamer capture device is preferably arranged 90° peripherally (e.g. circumferentially for a round basket) offset relative to a line extending through the bailing handle engagement points with the basket. The drain/steamer capture device is designed for providing a supporting/non-slide off relationship relative to the higher height cooking pot, which relationship can be established upon lifting the basket with the engaged grasp handle/bailing handle combination. The apertures in the basket are sufficient in number and placement to allow fluid drain off upon lifting the basket above an upper height of the cooking fluid (e.g., water or cooking oil) and steam entry. Apertures provided over the bottom and at least the lower half-height of the basket is preferred, with a full height extension of the holes over all the exposed area of the basket being more preferred. The holes are separated by sufficient material to provide the above noted high load capability (e.g. 20 lbs. or more) without material deflection.

The above noted generally transverse (70-100° offset) peripheral offset between the bailing handle engagement points and drain/steam capture device provides a desirable grasping/visibility relationship that allows for rapid lift up and side shift placement of the basket with drain/steam capture device. Also, the drain/steam capture device preferably has a pot rim capture width that provides for a minor tilting (1-25°) in the bottom edge of the basket to facilitating drain off of cooking fluid. This tilting also provides for the bottom edge of a basket to come in contact with an interior side wall of the preferred size pot for added stability (in conjunction with the capture device).

In an alternate embodiment of the invention the capture device has two (or more) capture devices with a second preferably diametrically opposed to the first end at a different height than the first. For example, if the first is within the top 20% of the basket, the second is placed within the top 50% and lower (from the basket's top edge) than the first. This provides added versatility to accommodate for different relative height spacing between the top of the cooking fluid and top of the pot. This also provides for added versatility as to accommodate different size pots (e.g., a 40 quart pot would have a different cooking fluid level to top of pot height value than a 30 quart pot of similar diameter).

In a first embodiment of the device the capture device is a monolithic drain and steamer hook device featuring a curved back wall secured (e.g., welded) to an upper external region of the perforated basket. The capture device further includes a pot upper edge contact portion that extends out radially away from the basket for a distance sufficiently to clear the thickness of the upper edge of (e.g., upper edge bead) the cooking pot and, more preferably, sufficient to provide the tilting relationship described above. To prevent the sliding off of the basket once placed into support contact with the upper edge of the cooking pot, a non-horizontal segment extends down

from the radial outer end of the pot upper edge contact portion. The downwardly extending component has an interior surface and at least part of that interior surface contacts the upper edge of the pot as the basket tilts into contact position. There is also preferably a curvature in the downwardly extending component corresponding to the curvature of the back wall of the capture device (and also the basket's).

The capture device is formed of a sufficiently strong enough material (e.g. a steel material or aluminum material at least as thick as the basket's main body) relative to its configuration to fully support a basket containing a large turkey (e.g., 15 to 20 or more pounds either in a pre-cooked state or a post-cooked state with absorbed cooking oil).

In one embodiment the capture device is a monolithic drain and steamer hook device featuring a curved back wall and, extending off of the common back wall, a first capture hook segment featuring an upper (e.g., horizontal) segment for contact with the upper edge of the pot receiving the basket and a pair of second capture hook segments that are less horizontal than the first and designed to prevent a slide off situation with respect to the first capture hook segment. The second capture hook segments are also preferably vertically oriented when in use or oblique (preferably in toward the pot's outer wall with enough clearance to receive the upper edge region of the pot or of less clearance with an outward curved bottom region for allowing an initial snap fit relationship relative to the top head of the pot). The first capture hook segment interlinks the second capture hook section along a base region of the same so as to define a border region of a notch formed between the two first capture hook segments. This arrangement is advantageous in that it provides good curved pot upper edge conformance and avoids basket rocking, while facilitating manufacture of the drain and steam hook. That is, a single piece can be bent or formed to define the entire drain and steamer hook device and then secured and the capture hook

segments readily conform to the curvature of the pot upon a bending of the back wall (i.e., upon a bending of the back wall the capture hook segments further separate outward relative to the central notch to go from a transverse to straight back wall to a transverse to the basket's curvature tangent relationship). In other words, due to a circumferential reconfiguring of the back wall to conform to the curvature of the basket main body, the second hook capture segments also assume a curvature by separating apart in the notch region to achieve a desired level of conformance to the curvature of the basket.

Preferably the capture hook segments are arranged such that the upper edge or curved bead of the pot comes in flush contact with the interior surface of the second hook capture segments. For instance, contact within a region extending from a central region of the interior surface of the second hook capture segments to the interior edge region of the second hook capture segments defining the notch there between. In this way capture device function as locking means in that they attach/conform to the upper edge of the pot in circumferentially spaced apart fashion to prevent not only radial sliding off but rocking of the basket in view of the above noted clamping point contact arrangement. By providing sufficient radial clearance between the first capture hook segment and thickness of the pots' upper edge, a tilting of the basket can be achieved to place the bottom edge of the basket in contact with the pot further enhances stability. The slot or notch extends between the interior side edges of the second capture hook segments as well as partially (e.g., 50% to 85% of the thickness) into the first capture hook segment to facilitate connection conformance during capture device attachment.

A preferred method of the present invention for forming the capture device is to form a cutout in a planar plate and then subjecting the cut plate to a die clamping operation. The bent

plate is then bent to conform to the curvature of the basket either during or prior to a fastening operation (e.g. a welding operation).

In an alternate embodiment, the capture hook arrangement is different in that two independent capture hooks are involved with each having their own upper capture hook segment and the bent radially farthest out capture hook segment extending down. The individual capture hook segments are circumferentially spread apart (e.g., within a 4 inch end to end circumferential spacing) in similar fashion to the above described capture hook segments and have a similar radial extension for the first capture hook segments to provide the above noted clamp and lock function between the pair of independent capture hooks and the upper circumference of the pot. They are however less desirable from the above described embodiment due to increased component and manufacturing requirements.

The capture device thus provides a secure location for placement of a basket with a heavy load into supporting contact with the pot above the top level of the cooking fluid so the cooking fluid can drain before final removal of the cooked food. In addition, the capture device is multi-functional in that it also provides a steamer hook which allows the basket to be supported above a lower level of steam source cooking fluid.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a cooking pot, drain and steamer hook basket and grab hook combination

Fig. 2 shows a drain and steamer hook basket combination

Fig. 3 shows a basket hooked onto the side of the pot draining a turkey

Fig. 4 shows a basket with turkey inside cooking pot being fried

Fig. 5 shows a basket hooked onto the side of the pot steaming clams

Figs. 6 and 7 show an alternate embodiment of the present invention.

Figs. 8 and 9 show another alternate embodiment of the present invention.

Fig. 10 shows a flat plate used for forming a capture device.

Fig. 11 shows a die operation for forming a bent plate configuration.

Fig. 12 shows the bent plate configuration produced by the die of Fig. 11.

5 Fig. 13 shows the bent plate configuration of Figure 12 being subjected to a curving operation.

Fig. 14 shows an alternative basket embodiment featuring two capture devices at different height levels.

Fig. 15 shows an alternate embodiment of the present invention featuring a pot oil drain spigot.

Fig. 16 shows the pot of Fig. 15 on a cooking burner stand with propane source and with a drain receptacle.

Fig. 17 shows an enlarged view of the pot drain assembly.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

This invention is directed at a fryer, boiler and steamer cooking apparatus 1 comprising basket 50 with bailing handle and drain/steamer hook or capture device 10. As shown in Figures 1-5, drain and steamer hook or capture device 10 allows for the basket 50 to clip or hook to the side of cooking pot 60. Reference 30 is the grab hook used to lower and remove the main body of basket 50 from the cooking pot 60. Reference 40 is the bailing handle that is attached to the basket 50. Figure 4 shows turkey 70 inside the basket ready for a deep oil fry while Figure 5 shows clams 75 ready to steam.

20 As shown in Figures 3 and 4, the height of the basket is sufficient to cover more than the lower half of a vertically oriented turkey. Figure 3 also shows oil level 80 after the basket is raised up and hooked onto the side of the cooking pot 60 while reference 90 shows the oil or water drippings from food back into the pot. Thus, there is avoided the dripping of oil or

cooking fluid in removing the basket with cooked food from the pot. Reference 100 in Figure 5 represents steam rising from water (cooking fluid) 110 when steaming seafood. While hooked, the bottom of the main body of the basket 112 is tilted such that the non-hooked side of the basket is below the horizontal so as to facilitate a more complete drain off of the cooking fluid.

5 Figures 6 and 7 illustrate an alternate embodiment of the present invention which has somewhat similar features as that above described with the generally common components indicated by the same reference number with an added dash designation. Like the first embodiment, the Figure 6 embodiment features a bailing handle 40' that is pivotably connected to reception holes in the basket as represented by reference number 108. The bailing handle 40' takes on a different configuration, however, with its vertical, parallel side extension and a straight triangular shaped cross over providing a grab hook reception area 20'.

10
15
20 In the first described embodiment drain hook 10 is a monolithic drain and steamer hook device featuring a curved back wall welded or otherwise fixed to the exterior of the basket at a point below (e.g. ¼ inch to 2 inches) the upper edge of the basket and preferably at a location between the upper basket edge and above a ¾ height level of the basket. With reference to Figures 12 and 13, an enlarged view of capture device 10 in a pre-complete (Fig. 12) and post-complete (Fig. 15) state is provided. Extending off of the common back wall 35 is capture hook segment 37 featuring an upper (e.g. horizontal) segment 39 for contact with the upper edge of the pot receiving the basket and a pair of second hook segments 41, 41' that are less horizontal than the first and designed to prevent a slide off situation with respect to the first capture hook segment. The second capture hook segments are also preferably vertically oriented when in use or oblique preferably in toward the pot's outer wall with enough clearance to receive the upper edge region of the pot (or an outward curved bottom region for allowing a snap fit relationship).

In addition, as part of the first capture hook segment 39, there is provided an integrating section 43 in the monolithic drain and steamer hook 10. Integrating section 43 defines an interior border region of notch 49 formed between the pair of second hook segments 41, 41'. The monolithic capture device arrangement shown in Figure 1 is advantageous in that it provides good pot upper edge conformance and avoids basket rocking, while facilitating manufacture of the drain and steam hook in that a single piece can be bent or formed and then secured (e.g., an intermediate weld) and the capture hook segments readily conform to the curvature of the pot upon a bending of the back wall (i.e., upon a bending of the back wall the capture hook segments further separate outward in a "transverse to the basket curvature tangent" relationship). Due to an outward circumferential spreading of the hook capture segments with the back wall the hook segments are able to conform well to the curvature of the supporting pot. This arrangement also provides for small radial clearance (e.g., ½ inch to 2 inches) between a centered basket's main body and interior of a cooking pot. This facilitates the providing of lesser diameter cooking pots that lessen the oil purchase requirements (e.g. 26 qt. pot) and yet have sufficient volume and height for covering a large turkey under the upper level of the oil at least 3 inches clearance to the upper level of the cooking pot.

Preferably the capture hook segments are arranged such that the upper edge or curved bead of the pot comes in contact with the interior surface of the hook segments 41 such as in the area extending from interior edges 101 and 103 of defining notch 49 the hook segments to external edge 105 and 107. With this two area contact to circumferentially opposite sides of the slot or notch 49 in the capture device, the metal drain hook segments function as locking means in that they attach/conform to the upper edge of the pot to prevent rocking of the basket in view of the above noted clamping point contact arrangement and circumferential spacing. The heat

resistant material chosen for the hook 10 (10' and 10'') is preferably a significantly strong enough metal material able to handle (maintain its original orientation upon release) the industry considered maximum turkey weight following absorption of oil (actually preferably at least 1.5 times or more that weight). While extending down vertically in this embodiment the radial outer most section of the hooks can also slope inward toward the basket with preferably an added outward curved lower edge to facilitate rapid positioning.

The capture hook arrangement 10' in Figure 6 and 7 is different in that two independent capture hooks are involved with each having their own upper capture hook segment and the bent radially farthest out capture hook segment extending down. The individual capture hook segments are circumferentially spread apart in similar fashion to the above described capture hook segments and have a similar radial extension for the first capture hook segments to provide the above noted clamp and lock function between the pair of independent capture hooks and the upper circumference of the pot. A four inch (outer edge to outer edge) circumferential spreading is suitable and places each hook segment within a common quadrant of the supporting pot.

Figures 8 and 9 illustrate an alternate design of the present invention which includes rigid vertical bailing extensions (40'') preferably fixed to the interior of the basket with fixation plates 120 which can be welded for example. The fixation points for both the pivoting and fixed ends of the bailing handles 40, 40' and 40'' are preferably 90 degrees offset to either side of the preferably single side steamer and drain hook device 10, 10', 10'' (unitary or two independent capture hook embodiments). The upper ends of bailing extensions 40'' have reception loops 31 for receiving the corresponding reception hooks 33 on the vertical legs extending off the single horizontal interconnector bar of grasp hook 30''. The embodiment in Figure 8 also shows a beaded upper basket edge.

Figures 10-12 illustrate one example of forming the monolithic capture device 10 shown in Figure 1. Flat plate 51 is shown in Figure 10 with dash lines 53 showing the notch region to be removed. Also, Figure 10 shows, with ghost lines, three equal area regions 55, 57, 59. As shown in Figure 10, the notch 53 extends in the interior middle region of the plate as to entirely pass through region 55 and partially (e.g. 40% to 85%) through region 57.

Figure 11 shows the plate 51 with cut-out 49 formed being subject to a die forming operation between male die member 61 and female die 63. Following movement of one or each relative to the other straight edge bent plate 37 is formed as shown in Figure 12.

Figure 13 illustrates a second die set 71 and 73 used to form the appropriate curvature in back wall 35 as well as the expanded notch 49 in so doing. Rather than the illustrated die 73, reliance can instead be placed upon the basket itself to which the conforming capture device is to be attached (with the corresponding curving die component being free or a component supporting a fastening means such as a spot weld head).

Figure 14 illustrates an additional embodiment of the invention featuring the same boiling handle 40 and basket combination as before but with a pair of capture devices 10, 81 provided on the main body of the basket. As shown in Figure 14, the two capture devices are secured to the basket at generally diametrically opposed locations (a preferred direct diametrical arrangement being preferred but not shown for greater visibility) and also at different height levels h_1 and h_2 with (h_2-h_1) preferably representing about a 1 inch to 4 inch difference. The difference in height provides for varying the relative height of the bottom of the basket 50 to the upper surface of the cooking fluid. This includes both the steaming cooking fluid level and also deep fry cooking oil levels which can vary depending upon how much oil is put in to deep fry and the dimensions of the cooking pot and the height of the turkey.

Figure 16 illustrates the basket in Figure 14 supported on the upper edge of cooking pot 91 on the lower basket positioned capture device 81. As seen from Figure 16, oil level 93 is just below the tilted bottom of basket 50", but sufficient enough to allow for the drain off of oil. Relative to this particular basket, pot and oil level arrangement, capture device 10 does not provide sufficient lift off of the basket bottom, but would provide a desirable height for steaming seafood or for a different pot/basket/oil level arrangement.

The capture device hooking of a basket allows for the drain off of cooking fluid including water used in boiling and cooking oil used in deep frying. Thus, there is avoided a mess of substantial cooking fluid dripping while avoiding the cook having to maintain a lifting position relative to a potentially heavy cooked food load such as a turkey.

Figures 15 and 16 illustrate a modified cooking apparatus 1' with pot 91 having a preferred embodiment of a cooking fluid drain off assembly 95. Drain-off assembly 95 is shown in Figure 15 to be positioned close to the bottom of pot 51 (preferably as close as possible while taking into consideration structural clearance and any bottom curvature of the pot) such as within 1 or 2 inches above the bottom of the pot.

Figure 17 illustrates drain off assembly 95 in this embodiment comprising ball valve 96 with on/off lever 107 (e.g. a 3/8" ball valve with 3/8" female pipe thread (FPT)). Compression adapter 97 (e.g. a 3/8" male pipe thread (MPT) x 3/8" compression adapter) is threaded through a hole drilled into the pot such that the adapter nut is on the interior side of the pot. A set of metal/nylon/nylon washers 99 are then provided between the pot's exterior and around the threaded male member of the compression adapter which threads into the female threads of ball valve 96 to provide a sealed attachment when lever 107 is in closed position. While a ball valve arrangement works well in starting and stopping flow alternate flow/no flow drain means

including other valve types and spigot arrangements can also be relied upon. Also, rather than reliance on fasteners like the washer and nuts shown in Figure 15 a direct weld to provide a sealed drain off arrangement can also be relied upon. The above noted sizing is well suited for a drain off of oil although larger size drain conduits (e.g. 25% to 150% larger) can also be relied upon if more rapid drain off is desired. The material of the drain off assembly should be able to handle both cooled off and not-cooled off oil temperatures (e.g., up to 500 degrees Fahrenheit)

Drain off assembly 95 provides an additional means for avoiding a mess, particularly when dealing with cooking oil which can be difficult to wipe up and remove, and avoids the cooker having to tilt or lift heavy objects such as a 40 quart pot with 4 to 5 or so gallons of cooking oil. Thus, in combination with the drain off basket with capture device and drain off assembly 95 the drainage of cooking fluid is both made easier and less messy. An example of the combination is shown in Figure 16 (although draining of the cooking oil is preferably carried out after the cooling of the cooking fluid, which is typically after removal of the basket following cooking oil drip off from the turkey shown). Figure 16 also illustrates, cooker stand 201 with fuel supply (e.g. propane gas) 203 extending to burner 205 of the outdoor cooker stand 201.

Figure 16 further shows lever 107 in an open position such that cooking fluid is free to pour out of pot 91 in free air flow down into a suitable receptacle (e.g. the original cooking oil 1 gallon jug – not shown). As also seen, the drain off assembly 95 is preferably generally 90° offset from the handle of the pot.

As an example of use of the combination illustrated in Figure 16, an appropriate amount of cooking oil (e.g. enough to cover over the turkey once the basket is fully immersed) is placed into pot 91 with valve assembly 95 closed. The burner 201 is then turned on to raise the cooking oil to a desired cooking temperature (e.g. 350 - 375°F). Once the cooking fluid reaches the

desired temperature, the prepared (seasoned) turkey is placed in basket 50" and with the grasp hook 30 and bail handle, the turkey and basket are lowered into the state represented by Figure 4. Upon passage of a suitable cooking time within the oil, the basket with turkey is raised with the grasp handle 30. The basket is then hooked to the side of the pot on a capture device (80 in the illustrated embodiment). After a short period (e.g. 30 seconds to 5 minutes), the cooking fluid has essentially dripped back into the pot from the basket and turkey. The basket with turkey is then moved to the desired turkey removal location and the turkey is removed from the basket. After a sufficient cooling period (e.g. a ½ hour to an hour), the oil in pot 91 is drained off by positioning a receptacle under valve assembly 95 and lever 107 is turned on to produce oil flow 111. The oil then drains until the receptacle is filled and the lever 107 is shut off to avoid any over fill. Additional receptacles are then filled in the above noted sequence until the oil level falls below the drain hole where upon there is little oil left allowing for easy tilting of the pot to complete drain off (either through the drain or out the open top of the pot). Figure 16 also shows an alternate embodiment of drain off means which includes a sealable receptacle 109 that is sufficiently sized to accommodate a complete single receptacle drain off. Also, a conduit can be threaded to the end of valve assembly 95 for insertion into or threading onto receptacle 113 (thus providing a sealed system). To speed up the drain off time, a pump (P) (e.g. a drill operated pump) can be placed in line or in fluid communication with conduit 115 and/or a larger sized drain conduit utilized as there is no concern for overfill particularly with a threaded receptacle connection.

As can be seen with each illustrated basket there is provided drain/steam holes or apertures 120 over essentially all of the side and bottom wall surfaces, although other

embodiments are considered under the present invention including baskets with only lower half apertures such as in the bottom only and/or the lower region of the side wall.

It will be understood that the embodiments shown and the procedures set forth above are intended to be illustrative only and are not intended as limiting the scope of this invention, it

5 being intended that all equivalents thereof be included in the scope of the appended claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219